

## Water Blasting Protection Boots

Up to 3000 Bar



Boots 3000 withstands "everything" within waterjetting on account of its fixed aluminium gaiters. The gaiters are moulded and jointed, which gives both excellent comfort and mobility. The Boots conform to the requirements set out in BGR 191 and EN 345-1 99A5 S5. The weight of each boot is 1 kg.

Size	Part No
42	92.00.0310-42
43	92.00.0310-43
44	92.00.0310-44
45	92.00.0310-45
46	92.00.0310-46
47	92.00.0310-47
48	92.00.0310-48

Tested and certified according to BGR 191.

Bar	Flow Rate l/min	Nozzle	Distance between nozzle and boots	Nozzle Speed	Reactions Force (N)
1700	20,0	Round 1 mm	75 mm	0,2 m/s	250
2500	19,0	Turbo 0,8 mm	75 mm	0,2 m/s	227
3000	19,0	Rotary 3x0,5 mm	75 mm	0,2 m/s	243
3000	16,2	Round 0,8 mm	75 mm	0,2 m/s	207

CE-marking: Approved according to the directive 89/686/EEC and BGR 191.

**KAMAT SU JETİ TEKNOLOJİSİ MAKİNA İNŞ. SAN. ve TİC. LTD. ŞTİ.**

